

/ Descriptions

Silicon NPN transistor in a TO-220 Plastic Package.


/ Features

Large current capacity with small package, low collector saturation voltage, pair with 2SA1129.


/ Applications

For low-frequency power amplifiers and mid-speed switching.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	M	L	K	J
h_{FE} Range	40 80	60 120	100 200	160 320


Parameter	Symbol	Typical Value	Unit
Collector to Base Voltage	V_{CBO}	100	V
Collector to Emitter Voltage	V_{CEO}		

/ Electrical Characteristic Curve


€



/ Package Dimensions



/ Marking Instructions



Note:


BR: Company Code

C2654: Product Type.

M: h_{FE} Classifications Symbol

****.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255 5

, Duration:5 0.5sec.
3. Cooling Speed: 2~10

/sec.

/ Resistance to Soldering Heat Test Conditions

270 5 10 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type 封装形式	Units/Tube 只/套管	Units 包装数量	Dimension 包装尺寸 (unit: mm ³)
----------------------	--------------------	------------	---