

/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.


/ Features

Low f_T .

/ Applications

Low frequency general-purpose amplifier applications.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	4	5	6	7
h_{FE} Range	90 180	135 270	200 400	300 600
Marking	L4H	L5H	L6H	L7H


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	55	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current	I_C	150	mA
Collector Current (Pulse)	I_{CP}	300	mA
Collector Power Dissipation	P_C	200	mW

/ Electrical Characteristic Curve




SOT-23

单位:  



/ Marking Instructions



L

4 h_{FE}

H


Note:

L Product Type Code

4 h_{FE} Classifications Symbol Code

H Company Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	(unit mm ³) Outer Box