

一、 描述 / Descriptions

SOT-89 NPN Silicon NPN transistor in a SOT-89 Plastic Package.


二、 特性 / Features

1、 与 2SA1201 互补。
High f_T , high V_{CEO} , small flat package, complementary pair with 2SA1201.


三、 应用 / Applications

Power amplifier applications.

四、 等效电路 / Equivalent Circuit



五、 引脚 / Pinning









PIN1 Base PIN 2 Collector PIN 3 Emitter

六、 标记 / Marking


h_{FE} Classifications Symbol	O	Y
h_{FE} Range	80 160	120 240
Marking	HCO * *	HCY * *

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	120	V
Collector to Emitter Voltage	V_{CEO}	120	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current-Continuous	I_C	800	mA
Collector Base-Continuous	I_B	160	mA
Collector Power Dissipation	P_C	500	mW
Collector Power Dissipation*	$*P_C$	1.0	W


Electrical Characteristic Curve



⌘ É Ò Ì ð / Package Dimensions



1. 1.1 / Marking Instructions



H

C


O

**

Note:

H: Company Code.

热冲击试验 / Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0l uhh,



9

Note:

- | | | | |
|---|------------|-----------|---|
| 1 | 25 150 | 60 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 /sec. | | 3. Cooling Speed: 2~10 /sec. |

4 热阻试验 / Resistance to Soldering Heat Test Conditions

±260±5 ±10±1 sec. Temp.:260±5 Time:10±1 sec

5 包装规格 / Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392

6 注意事项 / Notices