

/ Descriptions

TO-220F NPN Silicon NPN transistor in a TO-220F Plastic Package.


/ Features

2SB1063
Excellent h_{FE} , wide ASO, high f_T . complementary to 2SB1063.


/ Applications

High power amplifier application.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Q	P
h_{FE} Range	60 120	100 200

/ Absolute Maximum Ratings(Ta=25)


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	100	V
Collector to Emitter Voltage	V_{CEO}	100	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	5.0	A
Collector Current – Continuous(Pulse)	I_{CP}	8.0	A
Collector Power Dissipation	P_C	2.0	W
Collector Power Dissipation	$P_C(T_C=25)$	40	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=100V \quad I_E=0$			50	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=3.0V \quad I_C=0$			50	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=5.0V \quad I_C=1.0A$	60		200	
	$h_{FE(2)}$	$V_{CE}=5.0V \quad I_C=3.0A$	20			
	$h_{FE(3)}$	$V_{CE}=5.0V \quad I_C=20mA$	20			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=3.0A \quad I_B=0.3A$			2.0	V
Base to Emitter Voltage	V_{BE}	$V_{CE}=5.0V \quad I_C=3.0A$			1.8	V
Transition Frequency	f_T	$V_{CE}=5.0V \quad I_C=0.5A$ $f=1.0MHz$		20		MHz
Collector output capacitance	C_{ob}	$V_{CB}=10V \quad f=1.0MHz$		90		pF

2SD1499

/ Marking Instructions



BR

D1499

Q: h_{FE}

Note:


BR: Company Code.

D1499: Product Type.

Q: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

255±5

5±0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255±5

, Duration:5±0.5sec.
3. Cooling Speed: 2~10

/sec.

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units		Dimension		(unit mm ³)	
	Units/Bag	Bags/Inner Box	Units/Inner Box	In	17553	1F019TT7 1r6.48 6 7.44 r7315 0270700de90b4F0T4 1 T4.0075 0 T0.073.76 290.9603 Qur73.7teT4 1 T6 0 0 6.48 247.7431-0.9603