

/ Descriptions

SOT-23 N MOS N- CHANNEL MOSFET in a SOT-23 Plastic Package.


/ Features

500V HBM
Low on-resistance, fast switching speed, low voltage drive, easily designed drive circuits, easy to parallel. ESD protected up to 500V HBM .


/ Applications

Interfacing, switching.

/ Equivalent Circuit



/ Pinning




PIN1 G PIN 2 S PIN 3 D

/ Marking


Marking	KL
---------	----

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	± 20	V
Drain Current – Continuous	I_D	100	mA
Drain Current- Pulsed	I_{DP}^{*1}	400	mA
Reverse Drain Current – Continuous	I_{DR}	100	mA
Reverse Drain Current –Pulsed	I_{DRP}^{*1}	200	mA
Total Power Dissipation	P_D^{*2}		


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions




KL:

Note:

KL Package Type

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices