

78D05

Rev.J Jun.-2024



蓝箭电子
BLUE ROCKET ELECTRONICS

DATA SHEET

TO-252







Voltage Regulator in a TO-252 Plastic Package.

1.5A,


3-Terminal regulators ,outl8 RegSrrent up to .52A,in JJ-2.230030 TD-.0005 Tc.0028 Tw[Vteral rthermal-7.(overl)-4

Parameter

/ Electrical Characteristic Curve



/ Package Dimensions



单位: mm

[illegible]
$$T_0 \equiv 252$$

78D05

Rev.J Jun.-2024

() / Temperature Profile for IR Reflow Soldering(Pb-Free)

- Note:
- 1

150 180

60 90sec;

2

245±5

5±0.5sec;

3

2 10 /sec.
- 1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 ℃ Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box