



	! " # \$	% ! " & ' (	! ") * & + ,	- .	/ 0
1	232345422	166	7 8 9 .	: ; <	= > ?



Rev.A Jul.-2020

SOD-123 @ A A B C D E F G H I J

Silicon Diode in a SOD-123 Plastic Package.

K L M N O P Q R S T U V & U V W X Y J Z [E \] % ^ _ J ^ ` a b J

Low forward voltage drop, Guard ring construction for transient Protection. High Conductance, Also Available in Lead Free Version. HF Product.

D E F G H I c

Silicon diode.



PIN1:Cathode

PIN2:Anode





Parameter	Symbol	Rating			Unit
		B0520W	B0530W	B0540W	
Peak Repetitive Reverse Voltage	V_{RRM}	20	30	40	V
RMS Reverse Voltage	$V_{R(RMS)}$	14	21	28	V




Rev.A Jul.-2020

Rev.A Jul.-2020

<http://>



Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 1、预热温度 150 ~ 180℃，时间 60 ~ 90sec;
- 2、峰值温度 245±5℃，时间持续为 5±0.5sec;

Note:

- 1.Preheating:105~180℃, Time:60~90sec.
- 2.P e c 0