/ Descriptions

SOT-23 PNP Silicon PNP transistor in a SOT-23 Plastic Package.

/ Features

I_C BC817

High I_C ,complementary pair with BC817.

/ Applications

General power amplifier and switching applications

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	16	25	40
h_{FE} Range	100 250	160 400	250 600
Marking	H5A	H5B	H5C

Parameter

/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



H

5A

Note:

H: Company Code.

5A: Product Type Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



						Note:
1		25	150		60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2		245±5			5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3				2 10	/sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱

/ Notices