"Yت / Descriptions

SOT-89 PNP Silicon PNP transistor in a SOT-89 Plastic Package.

◕È / Features

, BC868

Low voltage, high current, Complementary to BC868.

٧ ﻉ / Applications

Low voltage, high current applications.

Л ف ً ڤ ≠ ع / Equivalent Circuit



ã ﻝ ŭ ً / Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

ł ˛ ʜ ב / Marking

Marking	HCEC

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-32	V
Collector to Emitter Voltage	V_{CEO}	-20	V
Emitter to Base Voltage	V		

≠ Ǝ ⁷Ạ´E ᛋ ƒ / Electrical Characteristic Curve



ᵘ ĖÒĻ ʃ / Package Dimensions



ł. Ł‘Ω / Marking Instructions



H

CEC

**

Note:

H:	Company Code.
CEC:	Product Type.
**:	Lot No. Code, code change with Lot No.

ѭ ʃ ╕ ẘ ´E ⅵ ʃ (ᾠ ᴈ) / Wh p shudwxuh Suriloh iru LU Uhio r z Vroghulq j+Se0luhh,



					Note:
1	25	150	60	90sec;	1.Preheating:25~150