WR0459I ḾḾÞ SQS ÆṀ ч s ‖ ㄱ Silicon PNP transistor in a

/ Package Dimensions



/ Marking Instructions



Note:	
BR:	Company Code
BD034:	Product Type.
R	h_{FE} Classifications Symbol
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ɬ ı ̀H ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ɬ ı ̀H ڑ ̀Y ʌ ʁ 5 ° 0.5sec;

3 ì ˙ ϒ ˛ ɔ ѡ ỷ ʁ 2 Ḱ 10 ɬ /sec.

Note:

1.Preheating:25~150 ɬ , Time:60~90sec.

2.Peak Temp.:255 ° 5 ɬ , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ɬ /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ɬ	̀H ڑ χ 10 ° 1 sec.	Temp.:270±5	Time:10±1 sec

/ Packaging SPEC.

̈Ω ţ ϒ Ł / BULK

Package Type	Units			Dimension (unit mm^3)
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	