

/ Descriptions

SOT23-6 N MOS N-channel Double MOSFET in a SOT23-6 Plastic Package.


/ Features

advanced trench technology to provide excellent $R_{DS(on)}$, low gate charge and operation with gate voltages as low as 2.5V. HF Product.



/ Applications

Use as a Battery protection , Switching application.

/ Equivalent Circuit



/ Pinning




/ Marking


Marking	8205
---------	------

BR8205


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions




8205

Note:

8205: Product Type Code.

****: Lot No. Code, code change with Lot No.

() / Whp shrdwxrh Prr iioh i rr IU Uhi orw Vroghriq j +Pe-Frhh,



Note:

- | | | | |
|---|---------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp:260±5	Time:1BT2((150)Tj/TT9413	1	T
-------	-----------	------------	--------------------------	---	---