Rev.B Mar.-2023

Parameter	Symbol	Rating	Unit
Working Voltage	V_{IN}	-0.3~+20	V
Thermal Resistance	$R_{\theta JA}$	200	/W
Power Consumption	P_W	500	mW
Storage Temperature	T_{STG}	-50~+125	
Working Temperature	T_A	-40~+85	

Notes: If the device operating conditions over the maximum rating of the above-mentioned conditions, may cause permanent damage to the device. The above parameters is only part of the operating conditions the maximum, we do not recommend the device running outside the scope of this specification. If the device to work long hours under the condition of absolute maximum limit, its stability may be affected.

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
The Output Voltage	V_{OUT}	V_{IN}=5.3V, I_{OUT}=10mA	3.234	3.30	3.366	V
The Output Current	I_{OUT}	V_{IN}=5.3V	300			mA
Load Regulation	V_{OUT}	V_{IN}=5.3V 1mA I_{OUT} 300mA		37	100	mV
Low Dropout	V_{DIF}	I_{OUT}=100mA, V_{OUT}=2%		195	300	mV
Static Power	I_{SS}	V_{IN}=5.3V		1.5	3.0	μA
Linear Regulation	V_{OUT}/V_{OUT}* V_{IN}	4.3V V_{IN} 20V I_{OUT}=1mA			0.2	%/V
The Input Voltage	V_{IN}				20	V
Temperature Coefficient	V_{OUT}/ T_A*V_{OUT}	V_{IN}=5.3V, I_{OUT}=10mA -40 T_A 85		100		ppm/

V_{IN}=5.3V 2%

V_{DIF}

Note: V_{DIF} is defined as the input voltage minus the output voltage that produces a 2% change in the output voltage from the value at V_{IN}=5.3V with a fixed load.

/ Basic Application



/ High Output Current Voltage Regulator



/ Short-Circuit Protection




A
a
E
E1
Max
0.56
A
4.4
4.7
a1
0.36



Q

7333

**

Note:

Q:	Automobile halogen-free product Code
7333:	Product Type
**:	Lot No. Code, code change with Lot No



Note:

1		150	200		60	120sec;	1.Preheating:150~200 , Time:60~120sec.
2		255±5				5±0.5sec;	2.Peak Temp.:255±5 , Duration:5±0.5sec.
3				2	10	/sec.	3. Cooling Speed: 2~10 /sec.

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ REEL

Package Type	Units					Dimension		(unit mm3)
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
SOT-89	1,000	7	7,000	6	42,000	7 ×12	180×120×180	390×385×205