

BRCO7350UT
Rev.A Mar.-2025

× ¢ , [T I Z O U T R (R U I Q * O G M X G S

, M y f / Marking Instructions

7350U *

^a ¢ y

7350U y ° Z W A

** y ¨ D Z W A k š ¨ D Z J

Note

7350U: Product Type Code

** : Lot No. Code, code change with Lot No

šWD t... • Ž Ć (x /) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

^a Ć y

10• Ä ½ “ † 150 ½180 - k ž • 60 ½90sec;

20• Q > “ † 245 r5 - k ž • 4 Ò 5 r0.5sec;

30•D N ò i Ò 0 , † 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“ † y 260 r5 -

ž • y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type	Units ;>û !H		Dimension ;>û p . (unit Åmm ³)
7>û ~ E	Units/Reel / --	Reels/Inner Box -- /-	