

/ Descriptions

TO-252 N

N-CHANNEL MOSFET in a TO-252 Plastic Package.



/ Features $R_{DS(on)}$ C_{rss} AEC-Q101

Low $R_{DS(on)}$, low gate charge, low C_{rss} , fast switching, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications

DC/DC

Suited for low voltage applications such as automotive, DC/DC Converters, and high efficiency switching for power management in portable and battery operated products, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit**/ Pinning**

PIN1 G

PIN 2 D

PIN 3 S

PIN 4 D

/ Marking

See Marking Instructions.


Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	40	V
Drain Current	$I_D(T_c=25\text{ }^{\circ}\text{C})$	164	A
Drain Current - Pulsed	I_{DM}		

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=20V$ $R_L=1\Omega$ $R_{GEN}=3\Omega$		11		ns
Turn-On Rise Time	t_r			11		
Turn-Off Delay Time	$t_{d(off)}$			40		
Turn-Off Fall Time	t_f			10		



/ Package Dimensions




单位: mm

Dimensions		In Millimeters		Dimensions		In Millimeters	
Min	Max	Symbol	Min	Max	Symbol	Min	Max
0.76	0.76	B	1.25	1.25	e1	2.24	2.34
0.70	0.70	C	0.60	0.60	e2	4.73	4.73
0.45	0.55	L	0.85	0.85	L3	10.25	10.25
0.45	0.45	L3	6.55	6.55	L	1.50	1.50
0.45	0.45	L3	6.75	6.75	L	0.60	0.60
0.10	0.10	D1	5.10	5.50	R	0.00	0.00

T0-252

/ Marking Instructions



BR

Q

025N04

Note:

BR: Company Code

Q: Automobile halogen-free product Code

025N04: Product Type Code

****: Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.