

BRCS030N04YBQ

Rev.A Nov.-2023






蓝箭电子
BLUE ROCKET ELECTRONICS




DATA SHEET

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	MC9A01T9y2M
-----------	--------	-----------------	-----	-----	-----	------	-------------

Electrical Characteristic Curve




/ Electrical Characteristic Curve



/ Package Dimensions


PDFN3X3A-8L

Unit:mm



Rev.00 202011

/ Marking Instructions



BR

Q

030N04

Note:


BR: Company Code

Q: Automobile halogen-free product Code

030N04: Product Type Code

****: Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--|
| 1 | 150 | 200 | 60 | 120sec; | 1.Preheating:150~200 , Time:60~120sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. | |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
PDFN3×3A-8L	5,000	2	10,000	6	60,000	13 ×12	360×360×50	380×335×366

/ Notices