



ММ Ё ъ ѓ ѡ з 1

$$U_{GV+r_q, \eta} \mid \mathfrak{z} \supset U_H \mid F_{uv} \mid \check{A} \mathfrak{H} \mathfrak{h} \mathfrak{y} \mathfrak{o} \mathfrak{d} \mid \mathfrak{h} \quad \mathfrak{f} \quad \beta$$

Ѓњ ђ я э ц б х н г д т GF2GF ċ "Ω ж "А Ã ꝑ β [OBJ] ♂ ⬢ ⚡ ŵ ċ "Ω | , ' н г Z ↑ [OBJ] € | ∂



x

x

x

x

Ƶ "Œ	Ÿ N	"Œ Œ	D Ÿ




±

/ Electrical Characteristics(Ta=25)

V_{DS}	I_N	f_{sw} : f_{T}	η_{ON}	ξ_{ON}	η_{OFF}	D_H
		Ω Ω				

BRCS070N03DP

/ Electrical Characteristic Curve



BRCS070N03DP

/ Package Dimensions

, M y f / Marking Instructions

BR
070N03

ª ¢ y
BR y , [W A
070N03 y ° Z W A
y Ÿ D Z W A k Š Ÿ D Z J

Note:
BR: Company Code
070N03: Product Type Code
*****: Lot No. Code, code change with Lot No

šWD t... •Žč (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

^ačy

1o• Ä½ “† 150 ½180 - kž • 60 ½90sec;

2o• Q> “† 245 r5 - kž • 4 Ò 5 r0.5sec;

3o•D N ò i Ò 0 ,† 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

605 r5 -