/ Descriptions

SOT-523 N MOS

N-CHANNEL MOSFET in a SOT-523 Plastic Package.

/ Features

Sensitive gate trigger current and Low Holding current.ESD protected,HF Product.

/ Applications

Intended for use in general purpose switching and phase control applications.

/ Equivalent Circuit



/ Pinning



PIN1 G PIN 2 S PIN 3 D

/ Marking

Marking	KN

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	50	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current	I_D	300	mA
Drain Current – Pulsed	I_{DM}	1200	mA
Power Dissipation	P_D	250	mW
Junction Temperature Range	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	
Thermal Resistance from Junction to Ambient	R JA	500	/W

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain–Source Breakdown Voltage	V_{DSS}	V_{GS}=0 I_D=250εA	50			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS}=0 V_{DS}=50V			1.0	εA
Gate-Source Leakage current	I_{GSS}	V_{DS}=0V V_{GS}=±20V			±2	εA
Static Drain-Source On-Resistance	$R_{DS(on)(1)}$	V_{GS}=10V I_D=0.3A		0.92	2.5	q
	$R_{DS(on)(2)}$	V_{GS}=4.5V I_D=0.2A		0.98	3	q
	$R_{DS(on)(3)}$	V_{GS}=2.5V I_D=0.01A		1.2	4.5	q
Drain-Source Diode Forward Voltage	V_{SD}	V_{GS}=0V I_S=300mA			1.2	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS} I_D=250uA	0.6	0.9	1.5	V
Input Capacitance	C_{iss}	V_{GS}=0V, f=1MHz, V_{DS}=15V		30		pF
Output Capacitance	C_{oss}			5.2		
Reverse Transfer Capacitance	C_{rss}			3.3		
Gate Resistance	R_g	V_{DS} = 0V, V_{GS} = 0V, f = 1MHz		157		
Turn On Delay Time	$t_{d(ON)}$	V_{GS} =5V, V_{DD}=5V, R_L=500 , R_G=10		15		ns
Rise Time	t_r			35		
Turn Off Delay Time	$t_{d(OFF)}$			80		
Fall Time	t_f			80		

/ Electrical Characteristic Curve







/ Electrical Characteristic Curve



Figure 7: Current De-rating

/ Package Dimensions





Dimensions In Inches		Symbol	Dimensions In Millimeters	
Min.	Max.		Min.	Max.
0.028	0.035	A	0.700	0.900
0.000	0.004	A1		
0.031		A2	0.700	0.800
0.028		b		
0.152		b1		
0.250		c		
0.004	0.008	c1		
0.000	0.007	D	0.700	0.900
0.228	0.244	E	0.579	0.620
0.150	0.157	E1	3.800	4.000
0.500 TYP.		e	1.270 TYP.	
0.090	0.110	e1	2.300	2.500
0.400 REF.		L	0.016 REF.	
0.260	0.460	L1	0.010	0.018
0°	8°	θ	0°	8°

/ Marking Instructions



KN

Note:

KN: Product Type Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)

					Note:
1	150	180		60 90sec;	1.Preheating:150~180 , Time:60~90sec.
2	245±5			5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3			2 10	/sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

605±5 (/ -5.7(Packagling)24286(SPEC.( )]TJ/TT7 1 Tf03.4485 32.3713 TD.0004 Tc-35.65309:602513T