



A	19-05-20				
B	2019-6-1 ⁴	1			
C	2021-3-1 ⁴	ALL	ZM18503PA		

/ Descriptions

P TO-252

P-CHANNEL MOSFET in a TO-252 Plastic Package.

/ Features

$R_{DS(on)}$


Low $R_{DS(on)}$, High Current Capability. Halogen-free Product.

/ Applications

/

AC-in load switch, Battery protection charge/discharge.

/ Equivalent Circuit



/ Pinning



PIN1 G

PIN 2 D

PIN 3 S

PIN 4 D

/ h_{FE} Classifications & Marking

See Marking Instructions.



BRCS40P03DP




DATA SHEET

Test Conditions	Min	Typ	Max	Unit
$V_{DS} = -0V$ $V_{GS} = 0V$ $f = 1.0MHz$		2530		pF
		790		
		450		
$V_{GS} = 0V$ $f = 1MHz$ $V_{DS} = 0V$		8		Ω
$V_{GS} = -10V$ $V_{DS} = -15V$ $I_D = -20A$		50	70	nC
		25	35	
		9		
		12		


/ Electrical Characteristic Curve




/ Package Dimensions



Symbol		Max		Min	
4.75	b	0.60	0.70	e2	4.43
9.95	b1	0.45	0.55	L1	9.45
0.45	0.55	L2	1.25	1.75	C
6.45	6.75	L3	0.60	0.80	D



/ Marking Instructions



BR

40P03

Note:

BR: Company Code

40P03: Product Type Code.

****: Lot No. Code, code change with Lot No.

