

BRCS50N06RA

Rev.A Sep.-2020



DATA SHEET

/ «Rev

Y

u

A	2020.09.09		BRCS50N06DP		

/ Descriptions

N TO-220

N-CHANNEL MOSFET in a TO-220 Plastic Package.

/ Features

$R_{DS(on)}$ C_{rss}


Low $R_{DS(on)}$, low gate charge, low C_{rss} , fast switching, Trench Technologies. Halogen-free Product.

/ Applications

DC/DC

Suited for low voltage applications such as automotive, DC/DC Converters, and high efficiency switching for power management in portable and battery operated products.

/ Equivalent Circuit



/ Pinning



PIN1 G

PIN 2 D

PIN 3 S

/ h_{FE} Classifications & Marking

See Marking Instructions.

BRCS50N06RA

Rev.A Sep.-2020




DATA SHEET

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DSS}	60	V
Drain Current	I		

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=30V$ $R_L=1.5\ \Omega$ $R_{GEN}=3\Omega$		8		ns
Turn-On Rise Time	t_r			5		
Turn-Off Delay Time	$t_{d(off)}$			30		
Turn-Off Fall Time	t_f			5.5		

/ Electrical Characteristic Curve



BRCS50N06RA

Rev.A Sep.-2020

/ Package Dimensions

