

/ Descriptions

TO-220AC



Schottky Barrier Diode in a TO-220AC Plastic Package.

/ Features

Low power loss,high efficiency .

/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit**/ Pinning**

PIN1 2 Cathode

PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions

BRLV10T100AC

Rev.H Apr.-2019

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
RMS Voltage	V_R	100	V
Average Forward Rectified Current	$I_{F(AV)}$	10	A
Peak forward surge current	I_{FSM}	150	A
Typical Thermal Resistance Junction to Case	R_{JC}	2.0	/W
Junction Temperature Range	T_J	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_R	$I_R=10\mu A$	100			V
Forward Voltage	V_F	$I_F=10A$			0.7	V
		$I_F=10A \quad T_C=125$			0.8	V
		$I_F=20A$			0.95	V
		$I_F=20A \quad T_C=125$			0.85	V
Peak Instantaneous Reverse Current	I_{RM}	$V_R=100V$ $V_R=100V \quad T$			0.1	mA

/ Electrical Characteristic Curve




Figure 1. Typical Forward Voltage

Figure 2. Typical Reverse Current




Figure 3. Current Regulation Characteristics

Figure 3. Current Regulation Characteristics




Figure 4. Forward Power Dissipation


BRLV10T100AC

Rev.H Apr.-2019

DATA SHEET



/ Marking Instructions



BR

LV10T100

Note:

BR:


Company Code

LV10T100

Product Type.

****:

Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)


Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.
/ BULK

Package Type	Units					Dimension		(unit mm ³)

/ TUBE

Package Type	Units					Dimension		(unit mm ³)

/ Notices