


BRMUR10120AC


Rev.B Jan.-2019

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Peak Reverse Voltage	V_R	1200	V
Average Rectified Forward Current	$I_{F(AV)} (T_c=110^\circ C)$	10	A


/ Electrical Characteristic Curve




/ Package Dimensions



/ Marking Instructions



公司代码	公司代码
EU	公司代码
P XU43453	公司代码
----	公司代码 公司代码
Note:	
BR:	Company Code
MUR10120	Product Type Code.
****:	Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)


说明

1. 预加热: 150~180 °C, Time: 60~90sec;
2. 峰值温度: 245±5 °C, Duration: 5±0.5sec;
3. 冷却速度: 2~10 °C/sec.

Note:

- 1.Preheating:150~180 °C, Time:60~90sec.
- 2.Peak Temp.:245±5 °C, Duration:5±0.5sec.
3. Cooling Speed: 2~10 °C/sec.

/ Resistance to Soldering Heat Test Conditions

温度: 270±5 °C 时间: 10±1 sec. Temp.: 270±5 Time: 10±1 sec

/ Packaging SPEC.

散装 / BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag	Bags/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Bag	Inner Box	Outer Box
TO-220/F/AC	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

管装 / TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-220/F/AC	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices