

Table 1 Absolute Maximum Ratings(Ta=25℃ ;)

Parameter		Symbol	Rating	Unit
Peak Pulse Power Dissipation on T _A =25℃ (Note 1,2,4, Fig1)		P _{PPM}	400	W
Peak Forward Surge Current (Note 3, Fig 4)		I _{FSM} (UNI)	60	A
Peak Pulse Current on 10/1000 us waveform (Note 1, Fig 3)		I _{PPM}	see Table 1	A
ESD Voltage per IEC6100-4-2	Contact	V _{ESD1}	f 30	KV
	Air	V _{ESD2}	f 30	KV
Typical Thermal Resistance Junction to Ambient(Note 2)		R _{JA}	100	/W
Operating Junction Temperature and Storage Temperature Range		T _j , T _{stg}	-65 ~ +150	

Note:

1. Non-repetitive current pulse, per Fig.3 and derated above T_A = 25℃ per Fig. 2.
2. Mounted on 5mm² copper pads to each terminal.
3. Peak Forward Surge Current : 8.3ms single half sine-wave Superimposed on rated load (JEDEC method).
4. Peak pulse power waveform is 10/1000 S.

Type		Reverse Stand-off Voltage	Breakdown Voltage		Test Current	Reverse Leakage	Max. Clamp Voltage	Peak Pulse Current	Package	
			V _{BR} @ I _T		I _T	I _R @ V _{RRM}	V _C @ I _{PP}	I _{PP}	SMA	
		V _{RRM}	Min	Max					Device Marking Ccode	
UNI	BI	V	V	V	mA	uA	V	A	UNI	BI
BR SMAJ5.0AQ	BR SMAJ5.0CAQ	5	6.4	7	10	800	9.2	43.5	AEQ	WEQ
BR SMAJ6.0AQ	BR SMAJ6.0CAQ	6	6.67	7.37	10	800	10.3	38.8	AGQ	WGQ
BR SMAJ6.5AQ	BR SMAJ6.5CAQ	6.5	7.22	7.98	10	500	11.2	35.7	AKQ	WKQ

Type		Reverse Stand-off Voltage	Breakdown Voltage		Test Current	Reverse Leakage	Max. Clamp Voltage	Peak Pulse Current	Package	
			V _{BR} @ I _T		I _T	I _R @ V _{R_{RM}}	V _C @ I _{PP}	I _{PP}	SMA	
		V _{R_{RM}}	Min	Max					Device Marking Ccode	
UNI	BI	V	V	V	mA	uA	V	A	UNI	BI

Ô ? d • Ž ¢ / Electrical Characteristic Curve

, M y f / Marking Instructions

AEQ

^ ¢ y
' + y ° Z W A
7 y V ñ —) í D } ö æ
**** y ÿ D Z W A k š Ÿ D Z J

Note:
AE y Product Type Code
Q: Automobile halogen-free product Code
**** y Lot No. Code, code change with Lot No

, M y f / Marking Instructions

WEQ

^a ¢ y
= + y ° Z W A
7 y V ñ —)í D } ö æ
**** y ÿ D Z W A k š ÿ D Z J

Note:
WE y Product Type Code
Q: Automobile halogen-free product Code
**** y Lot No. Code, code change with Lot No

šWD t...•Ž¢ (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

^a ¢ y

Note:

- 1o• Ä ½ “ † 150 ½200 - k ž • 60 ½120sec;
- 2o• Q > “ † 255 r5 - k ž • 4 Ò 5 r0.5sec;
- 1.Preheating:150~200 - , Time:60~120sec.
- 2.Peak Temp.:255 r5 - , Duration:5 r