

/ Descriptions

TO-220F

Schottky Diode in a TO-220F Plastic Package.

/ Features



Low forward voltage drop, low power losses, High efficiency operation.

/ Applications

OR-ing

DC-DC

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit**/ Pinning**

PIN1 Anode PIN 2 Cathode PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RM} V_{RSM} V_{DC}	100	V
RMS Voltage	V_{RMS}	70	V
Average Rectified Forward Current	$I_{F(AV)}$	2×5	A
Non Repetitive Peak Surge Current	I_{FSM}	80	A
Thermal Resistance Junction to Case	R_{JC}	4.5	/W
Junction and Storage Temperature Range	T_j T_{stg}	-40 +150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_{BR}	$I_R=1mA(T_a=25^\circ C)$	100			V
Forward Voltage	V_F	$I_F=3A(T_a=25^\circ C)$		0.59	0.65	V
		$I_F=3A(T_a=125^\circ C)$		0.53	0.60	V
		$I_F=5A(T_a=25^\circ C)$		0.69	0.75	V
		$I_F=5A(T_a=125^\circ C)$		0.61	0.65	V
Instantaneous Reverse Current	I_R Note 1	$V_R=100V(T_a=25^\circ C)$			50	A
		$V_R=100V(T_a=125^\circ C)$		3.0	10	mA


/Notes

1. α η β γ δ ϵ ζ η θ ι κ λ μ ν ξ $\omicron$ π ρ σ τ υ ϕ χ ψ ω

/ Package Dimensions



/ Marking Instructions



BR

LV10100

F:

CT:

Note:


BR: Company Code

LV10100: Product Type Code.

F Package Code

CT: Internal Structure

****: Lot No. Code, code change with Lot No.


() / Temperature Profile for Dip Soldering(Pb-Free)


Note:

- 1 25 150 60 90sec;
- 2 255±5 5±0.5sec;
- 3 2 10 /sec.

- 1.Preheating:25~150 , Time:60~90sec.
- 2.Peak Temp.:255±5 , Duration:5±0.5sec.
3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270±5

10±1 sec.

Temp.:270±5

Time:10±1 sec

/ Packaging SPEC.
/ BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type	Units	Dimension (unit mm ³)
Units/Tube /		