

/ Descriptions

WR0553I M M E = g ~ || 1

Schottky Diode in a TO-220F Plastic Package.

/ Features

$$H^* \rightarrow \mathbb{R} \cup \{H, \infty\} \quad \text{as } \omega \rightarrow \infty, \quad \Phi$$


Low forward voltage drop, low power losses, High efficiency operation.

/ Applications


[illegible]

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit



/ Pinning






PIN1	Anode	PIN 2	Cathode	PIN 3	Anode
------	-------	-------	---------	-------	-------

/ h_{FE} Classifications & Marking

٥ م ٦ ب " See Marking Instructions.


V_{TQ}
Parameter

/ Electrical Characteristic Curve




T U - 220 F


單位: 



/ Marking Instructions



BR	公司代码
LV10150	产品型号
FCT	封装形式
****	内部结构
Note:	
BR:	Company Code
LV10150:	Product Type.
F:	Package Code
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)


说明

1. 预加热: 25~150 °C, Time: 60~90sec;
2. 峰值温度: 255±5 °C, Time: 5~0.5sec;
3. 冷却速度: 2~10 °C/sec.

Note:

- 1.Preheating: 25~150 °C, Time: 60~90sec.
- 2.Peak Temp.: 255±5 °C, Duration: 5~0.5sec.
3. Cooling Speed: 2~10 °C/sec.

/ Resistance to Soldering Heat Test Conditions

测试条件: 270±5 °C, Time: 10±1 sec. Temp.: 270±5 °C Time: 10±1 sec

/ Packaging SPEC.

散装 / BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag	Bags/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

管装 / TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices