/ Descriptions

Schottky Barrier Diode in a TO-220 Plastic Package.

/ Features

Low power loss, high efficiency.

/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	150	V
Peak Repetitive Forward Current	$I_{F(AV)}$	10	A
Average Rectified Forward Current	I_{FRM}	10	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	150	A
Repetitive Peak Reverse Surge Current	I_{RRM}	0.5	A
Thermal Resistance Junction to Case	$R_{\theta Jc}$	2.5	/W
Junction and Storage Temperature Range	T_j,T_{stg}	-55 150	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Current Voltage	V_R	I_R=1mA	150			V
Forward Voltage	V_F	I_F=5A			0.88	V
		I_F=5A(Tc=125)			0.78	V
Instantaneous Reverse Current	I_R	V_R=150V			0.15	mA
		V_R=150V(Tc=125)			150	mA
Voltage Rate of Change	dv/dt				10000	V/μs

/ Electrical Characteristic Curve





/ Marking Instructions



Note:

BR:	Company Code
MBR10150	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.