MBRA10200CT

Rev.E Mar.-2016

蓝箭电子 BLUE ROCKET ELECTRONICS

DATA SHEET

/ Descriptions

WR0595 ṂṂ Ŀ ≠ ᵍ⁀ ‖ ㄱ

Schottky Diode in a TO-262 Plastic Package.

/ Features

ˆΩ ă Ң ı ѽ ' ≍


Low power loss, high efficiency.

/ Applications


ᵮ̂ ≍ ḛ Ң я ᶻ ɔ ㄴ Ω̃ ㄴ ‖ ㄱ ı ㅅ ㄴ ‖ ㄱ ı ℨ ĭ⁀ ‖ ㄱ

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit



/ Pinning



PIN1 χ Anode PIN 2 χ Cathode PIN 3 χ Anode

/ h_{FE} Classifications & Marking

ð м ヽ ب ″ See Marking Instructions.


/ Absolute Maximum Ratings(Ta=25)


v ̈Ω Parameter	ϒ N Symbol	̈Ω Ö Rating	D Ч Unit
Peak Repetitive Reverse Voltage	V_{RRM}	200	V
Average Rectified Forward Current	$I_{F(AV)}$	10	A
Peak Repetitive Forward Current	I_{FRM}	10	A
Non Repetitive Peak Surge Current	I_{FSM}	150	A
Peak Repetitive Reverse Surge Current	I_{RRM}	0.5	A
Thermal Resistance Junction to Case	$R_{\theta Jc}$	2.5	/W
Junction and Storage Temperature Range	T_j T_{stg}	-65 150	


/ Electrical Characteristics(Ta=25)


v ̈Ω Parameter	ϒ N Symbol	╜ : ̊ ţ Test Conditions	ω ņ Ö Min	Ɛ ʒ Ö Typ	ω ᶻ Ö Max	D Ч Unit
Reverse Voltage	V_R		200			V
Forward Voltage	V_{FM}	I_F =5.0A(T_C=25)			0.99	V
		I_F =5.0A(T_C=125)			0.87	V
Instantaneous Reverse Current	I_{RM}	V_R=200V(T_C=25)			0.15	mA
		V_R=200V(T_C=125)			150	mA
Voltage Rate of Change	dv/dt				10000	V/μs


/ Electrical Characteristic Curve













/ Marking Instructions



◌̇ ̋ χ	
EU χ	ꟻ ʒ ᴎ Γъ
P EUD43533 χ	ꟻ ꞩ ᵝ ȝ ᴺ
FW=	ꟻ ɲ ᶇh ᒧ ⚌
---- χ	ꟻ ꞉ ꞩ ᾐ ᴺ Γъ ꞉ ₡ ꞉ ꞩ ᾐ ᴺ Ψ ᖘ
Note:	
BR:	Company Code
MBRA10200 χ	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı `H ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ł ı `H ڑ `Y ﾊ ㎛ 5 ° 0.5sec;

3 ì ˙ ｲ ˛ ɔ ﻉ ỷ ㎛ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:255 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ł `H ڑ χ 10 ° 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

˛ ｱ ｬ Ł / TUBE

Package Type	Units					Dimension (unit mm³)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box

/ Notices