WR0584 ṂṂ Ŀ QSQ ӕṀ ɥ s Ⅱ ˥ Silicon NPN transistor in a TO-251 Plastic Package.

љ WLS75FL Ӣ ´
Complement to TIP42CI.

ҭ ᴀ I ' ˧ ớ Ầ Ꙕ ῢ ⱬ

v ῞Ω̦ Parameter	ɭ ᴺ Symbol	῞Ω̦ Ӫ Rating	ᴅ Ɉ Unit
Collector to Base Voltage	V_{CBO}	100	V
Collector to Emitter Voltage	V_{CEO}	100	V
Emitter to Base Voltage	V_{EBO}	5	V

/ Package Dimensions



/ Marking Instructions



ب ˝ χ

EU χ	Ж ʅ ᴎ Пƅ
WLS74F χ	Ж ғ ᵝ ʒ ᴺ
---- χ	Ж ꟷ ғ ή ᴺ Пƅ ι ɞ ꟷ ғ ή ᴺ Ψ ק

Note:

BR:	Company Code
TIP41C:	Product Type.
****:	Lot No. Code, code change with Lot No.

(　　) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ	Note:
1 ĺ ♬ □ ẙ 25 Ḱ 150 ɫ ı `H ڗ 60 Ḱ 90sec;	1.Preheating:25~150 ɫ , Time:60~90sec.
2 Ś Ӫ □ ẙ 255 ° 5 ɫ ı `H ڗ ʿY ɅI ѭ 5 ° 0.5sec;	2.Peak Temp.:255 ° 5 ɫ , Duration:5 ° 0.5sec.
3 ì ˙ Ɣ ˛ ɔ ﻫ ẙ ѭ 2 Ḱ 10 ɫ /sec.	3. Cooling Speed: 2~10 ɫ /sec.

/ Resistance to Soldering Heat Test Conditions

□ ẙ χ 270 ° 5 ɫ　　`H ڗ χ 10 ° 1 sec.　　Temp.:270±5　　Time:10±1 sec

/ Packaging SPEC.

̏Ω ʈ ɣ Ŀ / BULK

Package Type	Units					Dimension (unit mm³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-251	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195

˃˅ Ɂ ɣ Ŀ / TUBE

Package Type	Units	Dimension (unit mm³)
	Units/Tube /	